

PRESSA PIEGATRICE SINCRONIZZATA BEYELER 3000X150 Ton

6 ASSI (Y1,Y2,X,R,Z1,Z2) - INCAVO 600 mm - CNC CYBELEC - BOMBATURA
IDRAULICA - USATA ANNO 1999





36 CE

CONSTRUITO DA BEYELER GmbH MÜHLHÄUSER STRASSE 3 D-98567 GÖTTA GERMANY
 FORNITO E-ASSISTITO DA
 RASKIN BEYELER ITALIA srl VIA L. BERTELLI 8 40068 S. LAZZARO DI SAVENA (BO)
 +39 [0] 51 450901 +39 [0] 51 451853

TYPE	PR 6	TIPO	NO.	99/420/036
YEAR	1999	ANNO	AR.	1999
MASS (KG)	10 000	MASSA (KG)	10 000	GEWICHT (KG)
VOLTAGE	400 V	TENSIONE	NETZSPANNUNG	FREQUENCY
POTEE (KW)	11-KW	POTENZA	STROMVERBRAUCH	3 50 HZ
MAX FUSE	35 AT	FUSIBILE MAX	MAX SÄKERUNG	
MAX AIR PRESSURE (BAR)	8	PRESSURE MAX (BAR)	MAX LUFT DRUCK (BAR)	
MAX. MAT. THICKNESS (MILD ST. 450mm)		SPESORE MAX (ACCIAIO ST. 450mm)		
MAX. MATERIAL THICKNESS (BAUSTAHL 450mm)		MAX. MATERIALDIKKE (ST. 450mm)		

MACHINE LIFTING POINTS MARKED IN RED
 PUNTI DI SOLLEVAMENTO MACCHINA SEGNA TI IN ROSSO
 POINTS D'ELINGAGE REPRES EN ROUGE
 ANHÄNGEPUNKTE. ROT MARKIERT

PRESSBRAKE ONLY / PRESSE PLEUSE SEULEMENT / NUR ABKANTPRESSE SOLO PER PIEDGATRICI / ENOST KANTPRESSE / LITSLUITEND KANTPERS			
FORCE (kN)	1500	POTENZA (kW)	215
UPPER BEAM (kg)		LOWER BEAM (kg)	
MAX. CLOSING SPEED (mm/s)	200	VELOCITÀ DI CHIUSURA (mm/s)	
PRESSURE SPEED (mm/s)	1-10	VELOCITÀ DI PRESSIONE (mm/s)	
MAX. IDA STOP TIME (ms)	110	MAX. TEMPO DI STOP (ms)	
MIN. BEARING DISTANCE (mm)	350	MIN. DISTANZA DI PORTATA (mm)	



